

# Evergreen

## Description

Highly prized by individuals, the Evergreen is a useful product to provide an original key outdoor.

The products are similar to concrete paving stones but are hollow and grid-like. Evergreen (grass pavers) are mainly used in parking areas, hotel pathways and IRS developments.

As they are hollow, they can be filled with soil and planted with grass or flowers, allowing courtyards, pathways and parking areas to remain green.

- Size: 600mm x 400mm x 120mm high

## Technical Specifications

- Tolerances on work sizes

Dimension Maximum	Dimensional Deviation
Length	+3mm – 5mm
Width	+2mm – 2mm
Height	+3mm – 5mm

- Weight of UBP Evergreen: ±45kg
- Compressive strength of Evergreen: 30MPa
- Reinforcement: None
- Curing period: 7 days of curing in yard prior to delivery

## Materials Specifications

- Cement  
ORDINARY PORTLAND CEMENT (CEM I – 42.5N)  
Compliance with BS EN 197-1:2000 – Cement. Composition, specifications and conformity criteria for common cements.
- Aggregates  
UBP AGGREGATES (Rocksand 0-4mm & Coarse Aggregate 4-6mm)  
Compliance with BS 882: 1992 – Specification for aggregates from natural sources for concrete.
- Water  
BOREHOLE – Clean and free from any harmful amounts of deleterious matter, either in suspension or in solution controlled each month by external laboratories.

## Test and Compliance Certificates

Appropriate certificates are issued upon request. In case of no particular specifications / requirements on the product, the test and compliance certificates will be according to BS EN 1338:2003.

